

10/31/01

STABILITY:	Stable
HAZARDOUS POLYMERIZATION:	Will not occur
HAZARDOUS DECOMPOSITION PRODUCTS:	Carbon dioxide, carbon monoxide, hydrogen chloride, oxides from stabilizers
CONDITIONS TO AVOID:	Excessive heat, poor ventilation
INCOMPATIBILITY:	Strong oxidizing agents

---

#### SECTION VI - SPILL OR LEAK PROCEDURES

---

STEPS TO BE TAKEN IN CASE OF SPILL: Dike area to contain spill,  
salvage as much as possible for reuse, use absorbant to clean up  
remainder or small spills

WASTE DISPOSAL METHOD: In accordance with local, state, and federal  
regulations

---

#### SECTION VII - HEALTH DATA

---

ROUTES OF ENTRY: EYES - SKIN - INHALATION - INGESTION

EFFECTS OF OVEREXPOSURE: EYES - May cause irritation  
SKIN - May cause irritation, defatting, or dermatitis  
INHALATION - May cause irritation of respiratory tract, narcosis, or  
headaches  
INGESTION - May cause nausea, cramps, and diarrhea

EFFECTS MAY BE ACCELERATED BY HIGHER PRODUCT TEMPERATURES DURING THE  
MANUFACTURING PROCESS.

FIRST AID: EYES - Immediately flush with plenty of water. Get medical attention.

SKIN - Remove contaminated clothing and launder before reusing.

Wash affected area with plenty of soap and water.

INHALATION - Remove to fresh air. If necessary, give artificial  
respiration. Get medical attention.

INGESTION - Induce vomiting and dilute by drinking water. Never give  
liquids to an unconscious person. Get medical attention.

---

#### SECTION VIII - SPECIAL PROTECTION INFORMATION

---

RESPIRATORY PROTECTION: NIOSH/MSHA approved respirator suitable for  
concentrations and types of air contaminants encountered

VENTILATION: Local mechanical exhaust ventilation recommended

GLOVES: Impervious (neoprene)

EYE PROTECTION: Chemical goggles/glasses

OTHER EQUIPMENT: Safety shower and/or eye wash station

---

PRODUCT NAME: CLEAR 60 SA MEDICAL PLASTISOL  
PRODUCT NUMBER: PJJ 113 Series

---

#### SECTION IX - SPECIAL PRECAUTIONS

---

HANDLING AND STORAGE PRECAUTIONS: Keep container air tight in a dry

10/31/01

area away from heat and water when not in use. Practice "good" industrial housekeeping and hygiene.

---

SECTION X - ADDITIONAL INFORMATION

---

This product contains the following toxic chemical category(ies) subject to the reporting requirements of SARA Title III Sect. 313 (max percent by weight)

Di(2-ethylhexyl)phthalate is 43.2%

THIS INFORMATION IS TAKEN FROM SOURCES OR BASED UPON DATA BELIEVED TO BE RELIABLE; LOES ENTERPRISES INC.; MAKES NO WARRANTY AS TO THE ABSOLUTE CORRECTNESS OR SUFFICIENCY OF ANY OF THE FOREGOING OR THAT ADDITIONAL OR OTHER MEASURES MAY NOT BE REQUIRED UNDER PARTICULAR CONDITIONS.